



US006354196B1

(12) **United States Patent**
Malmberg et al.

(10) **Patent No.:** **US 6,354,196 B1**
(45) **Date of Patent:** **Mar. 12, 2002**

(54) **APPARATUS FOR GAS TREATMENT OF PRODUCTS**

(75) **Inventors:** Jonny Malmberg; Per Blixt, both of Helsingborg (SE); Jun A Hucker, Kirkland; Rick Wilson, Kent, both of WA (US)

(73) **Assignee:** Frigoscandia Equipment A/S, Helsingborg (SE)

(*) **Notice:** Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) **Appl. No.:** 09/889,672

(22) **PCT Filed:** Jan. 20, 2000

(86) **PCT No.:** PCT/SE00/00110

§ 371 Date: Jul. 19, 2001

§ 102(e) Date: Jul. 19, 2001

(87) **PCT Pub. No.:** WO00/42869

PCT Pub. Date: Jul. 27, 2000

(30) **Foreign Application Priority Data**

Jan. 20, 1999 (SE) 9900166

(51) **Int. Cl.⁷** A23L 1/00; A23L 1/01; A23L 3/36; F25D 3/11; F25D 23/02

(52) **U.S. Cl.** 99/443 C; 99/386; 99/476; 99/477; 126/21 A

(58) **Field of Search** 99/386, 443 R, 99/443 C, 476, 477-479; 126/21 A; 219/388, 400

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,817,875 A * 8/1931 Broadbent 99/476

3,813,895 A 6/1974 Klee et al.
3,908,533 A * 9/1975 Fagerstrom 99/443 C
3,991,737 A * 11/1976 Del Fabbro 126/21 A
4,368,664 A * 1/1983 Smith 99/443 C
4,478,141 A * 10/1984 Svensson 99/474
4,576,090 A * 3/1986 Burtea 99/443 C
4,679,542 A 7/1987 Smith et al.
4,779,524 A * 10/1988 Wade 99/476
4,831,238 A * 5/1989 Smith 219/388
4,873,107 A * 10/1989 Archer 99/477
4,909,430 A * 3/1990 Yokota 219/388
4,951,648 A * 8/1990 Shukla 99/443 C
4,986,174 A * 1/1991 Gongwer 99/386 X
5,231,920 A * 8/1993 Alden 99/475
5,408,921 A 4/1995 Persson et al.

FOREIGN PATENT DOCUMENTS

EP 0 249 323 A1 12/1987

* cited by examiner

Primary Examiner—Timothy F. Simone

(74) *Attorney, Agent, or Firm*—Browdy and Neimark

(57) **ABSTRACT**

An apparatus for gas treatment of products rises a housing having top, bottom and side walls; a conveyor belt for transporting the products along a first path in the housing; a tunnel having perforated walls and enclosing the conveyor belt along the first path; a gas circulation device communicating with the tunnel via the perforated walls for circulating gas into the tunnel in the form of gas jets impinging upon the products carried by the conveyor belt, and out of the tunnel in a return channel back to the gas circulation device; and a gas conditioning device positioned in the return channel. At least one substantially vertical part of the connecting walls of the high-pressure chamber is removable so as to provide access to the inside of the pressure chamber, and at least one of the side walls of the housing along the high-pressure chamber may be movable so as to widen the space between at least one wall and the high-pressure chamber.

16 Claims, 2 Drawing Sheets

